



SHOWN ENERGIZED

Model #	Net Pull Force (lbs./newtons)	Net Hold Force (lbs./newtons)	Max. Stroke (inch [mm])	Voltage	Coil Resis. (ohms)	Pull-in (amps)	Hold (amps)	Spring	Boot	Comments & Features
P610-A5V12	15/66.7	23/120	1.00 [25,4]	12 VDC	.25/12	48	1	No	Yes	
P610-A5V24	15/66.7	23/120	1.00 [25,4]	24 VDC	.96/49.5	25	.48	No	Yes	
P610-B5V12	13/58.7	16.5/73.4	1.00 [25,4]	12 VDC	.25/12	48	1	Light	Yes	
P610-B5V24	13/58.7	16.5/73.4	1.00 [25,4]	24 VDC	.96/49.5	25	.48	Light	Yes	
P610-C5V12	12.5/55.6	13.5/60.0	1.00 [25,4]	12 VDC	.25/12	48	1	Heavy	Yes	
P610-C5V24	12.5/55.6	13.5/60.0	1.00 [25,4]	24 VDC	.96/49.5	25	.48	Heavy	Yes	
P610-A5V00	16.8/74.3	42.8/190	1.00 [25,4]	108 VDC	19.7	5.4	.81	No	Yes	S500-A300 module
P610-A18V12	15/66.7	23/120	1.00 [25,4]	12 VDC	.25/12	48	1	Opt.	Yes	