



SHOWN ENERGIZED

Model #	Net Pull Force (lbs./newtons)	Net Hold Force (lbs./newtons)	Max. Stroke (inch [mm])	Voltage	Coil Resis. (ohms)	Pull-in (amps)	Hold (amps)	Spring	Boot	Comments & Features
P613-A5V12	21/93.4	40/178	1.50 [38,1]	12 VDC	.176/13.6	69.1	.88	No	Yes	
P613-A5V24	21/93.4	40/178	1.50 [38,1]	24 VDC	.66/50	36.8	.48	No	Yes	
P613-B5V12	21/93.4	33/147	1.50 [38,1]	12 VDC	.176/13.6	69.1	.88	B	Yes	
P613-B5V24	21/93.4	33/147	1.50 [38,1]	24 VDC	.66/50	36.8	.48	B	Yes	
P613-C5V12	20/89.0	29/129	1.50 [38,1]	12 VDC	.176/13.6	69.1	.88	C	Yes	
P613-C5V24	20/89.0	29/129	1.50 [38,1]	24 VDC	.66/50	36.8	.48	C	Yes	
P613-D5V12	20/89.0	24/107	1.50 [38,1]	12 VDC	.176/13.6	69.1	.88	D	Yes	
P613-D5V24	20/89.0	24/107	1.50 [38,1]	24 VDC	.66/50	36.8	.48	D	Yes	
P613-E5V12	14/62.3	27/120	1.50 [38,1]	12 VDC	.176/13.6	69.1	.88	E	Yes	
P613-E5V24	14/62.3	27/120	1.50 [38,1]	24 VDC	.66/50	36.8	.48	E	Yes	
P613-F5V12	17/75.6	30/133	1.50 [38,1]	12 VDC	.176/13.6	69.1	.88	F	Yes	
P613-F5V24	17/75.6	30/133	1.50 [38,1]	24 VDC	.66/50	36.8	.48	F	Yes	